

KASI LTD. ORDER FORMphone (+359 2) 8629274; fax: (+359 2) 8685169; e-mail: kasi@intech.bg

CONTRACTOR	
Company name	
Phone number	
Fax number	
e-mail	
Contact person	
Date of the filling of the order	
List of orders (fill in a column for each separate type)	
Name of the PCB file	
Repeat order without changes (yes/no)	
Deadline, weeks	
Quantity PCBs, pcs	
Measuring unit (only for PCAD - mm, inch etc.)	
Exact dimension X, mm	
Exact dimension Y, mm	
Thickness, mm (standard 1.6, additional price for 0.8, 1.2, 2.0)	
Format (GERBER ACCEL PCAD PCAD8)	
Base material	
Quantity of the layers (2 4 6 8)	
Solder resist on copper (yes/no)	
Quantity of legend layers	
Goldplating, area, mm ²	
Electric test (yes/no)	
Min. space between conductors, mm	
Min. conductors, mm	
Min, plated hole, mm	
Pad at min. plated hole, mm	
Thickness of copper foil, microns	
List of not-plated holes, mm	
Internal routing (yes/no)	
Plan for next order, pcs	
Final finishing	
Other conditions	
General parameters of board	
Drill file contains diameters of drills or holes	<i>holes</i>
Tolerance thickness of board, mm	<i>+ - 0,15</i>
Tolerance routing of board, mm	<i>-0,1</i>
Tolerance of diameter after metalization, mm	<i>+ -0.05 mm</i>
Tolerance center plated holes, mm	<i>+ -0.02 mm</i>
Tolerance center unplated holes, mm	<i>+ -0.2 mm</i>
Tolerance of conductor thickness, mm	<i>-0,05</i>
Radius of inner angles not more that	<i>1.0 mm</i>

